

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1. (previously presented): An ATM switching equipment comprising:  
a switching network;  
an input interface unit including an input processing unit;  
an output interface unit including an output processing unit;  
a microprocessor;  
a server switching unit comprising:  
an AAL2 switcher that is connected to the switching network via a first interface;  
an input processing unit to which said AAL2 switcher is connected; and  
an output processing unit to which said AAL2 switcher is connected;  
said switching equipment being configured to write a new VPI/VCI information,  
including VP/VCI bits, for a further connecting section into cells of arriving data streams upon  
utilization of routing tables,  
said AAL2 switcher being configured for simultaneous processing of a maximum  
plurality of incoming connections, an AAL2 routing list being provided for each of said  
incoming connections;  
said AAL2 switcher being connected to said switching network without requiring  
recognition of all VPINCI bits in the AAL2 switcher; and  
said microprocessor limiting the number of bits representing VPINCI bits from among  
VPI/VCI bits transmitted in a header of ATM cells to be interpreted according to a number of  
ATM connections available for processing, as indicated in said AAL2 routing lists, so that said  
first interface considers corresponding VPI/VCI bits.

Claim 2. (previously presented): The ATM switching equipment according to  
claim 1, wherein said first interface is a UTOPIA interface.

Claim 3. (previously presented): The ATM switching equipment according to claim 1, wherein a single virtual path is established between said switching network and said server switching unit.

Claim 4. (previously presented): The ATM switching equipment according to claim 1, further comprising:  
buffer memories which are allocated to said routing lists; and  
a section of an AAL2 packet of an ATM cell being writable into said buffer memories, said section being readable from said buffer memories when processing a next-successive ATM cell and for completion of a remainder of said AAL2 packet.

Claim 5. (new): An ATM switching apparatus, comprising:  
a microprocessor; and  
a server switching unit, comprising:  
an input processing unit;  
an AAL2 switcher that is coupled to the input processing unit, and is further coupled to a switching network via a first interface;  
an output processing unit, coupled to the AAL2 switcher, wherein the AAL2 switcher simultaneously processes a maximum plurality of incoming connections, and wherein an AAL2 routing list is provided for each of the incoming connections;  
wherein the ATM switching apparatus writes new VPI/VCI information including VPI/VCI bits for a further connecting section into cells of arriving data streams using routing tables, and wherein the microprocessor limits the number of bits representing VPI/VCI bits from among VPI/VCI bits transmitted in a header of ATM cells to be interpreted according to a number of ATM connections available for processing as indicated in the AAL2 routing lists, so that the first interface considers corresponding VPI/VCI bits.